



SH/TH

SAFETY DEVICE



- M18 Models 10 m (axial optic) and 5 m (radial optic) operating distance
- M30 models 60 m operating distance
- EN50100 Category 2 and Category 4 compliant

- LED indicators
- Plastic and Metal Housing
- Inputs and Outputs IEC61131-2 compliant and adaptable with any safety module
- To be used together with a Category 2 or Category 4 safety control unit to obtain a safety system EN ISO 13849 compliant



CODE DESCRIPTION

SH 2 / E - 0 E - IC

series	SH	M18 safety photocell							
	TH	M30 safety photocell							
type	2	Type 2, 123 kHz modulation							
	6	Type 4, 123 kHz modulation							
	4	Type 4, 123 kHz modulation							
model	E	Emitter unit							
	R	Receiver unit							
housing	0	Plastic housing, axial emission							
	1	Metal housing, axial emission							
	2	Plastic housing, radial emission							
	3	Metal housing, radial emission							
output connection	K	M2 radial connector output							
	E	M12 connector output							
logic	IA	Emitter Test Input Logic L = light H = dark, Receiver Output Logic: L = light, H = dark							
	IC	Emitter Test Input Logic H = light L = dark, Receiver Output Logic: H = light, L = dark							

TECHNICAL SPECIFICATIONS

	SH2/E-**IC		SH2/R-**IC	
	SAFETY TYPE 2			
GENERAL DATA				
Operating principle	Emitter		Receiver	
DETECTION CAPABILITIES				
Nominal sensing distance	0 ... 10 m			
Controlled height	Single-beam			
Thermal drift	≤ 10% Sr			
EMISSION DATA				
Emission	Red			
Effective beam angle	≤ ±5 ° (SH2/*-**IC)			
SAFETY PARAMETERS				
Type	2 (IEC 61496)			
PL	c (EN ISO 13849)			
PFHd	1 x 10-6			
INPUT/OUTPUT				
Output type			Totem-pole	
HMI/UI				
LED indicators	Yellow (power)		Yellow (alignement)	
ELECTRICAL DATA				
Supply voltage	10 ... 30 Vdc			
Maximum residual ripple	5%			
Maximum No-load absorption	25mA			
Maximum DC output voltage drop			2.5 V @ IL=50mA	
Maximum DC output voltage drop			70 mA	
MECHANICAL DATA				
Dimensions	M18x1 / L=98 mm			
Diameter / Dimensions	M18			
Housing material	PBT, Metal			
Active part material	Glass			
ENVIRONMENTAL DATA				
Operating Temperature	-20 ... 55 °C (without freeze)			
Mechanical Protection	IP67			
Storage temperature max.	-40 ... 75 °C			
Shocks and vibrations	IEC60068-2-6			
Humidity	15 ... 95 % no condensation			

TECHNICAL SPECIFICATIONS

	SH4/E-***IA	SH4/E-***IC	SH4/R-***IA	SH4/R-***IC
	SAFETY TYPE 4			
GENERAL DATA				
Operating principle	Emitter		Receiver	
Control units to be used	SBCR03 Series		SBCR03 Series	
DETECTION CAPABILITIES				
Nominal sensing distance	0 ... 10 m			
Controlled height	Single-beam			
Thermal drift	≤ 10% Sr			
EMISSION DATA				
Emission	Red			
Effective beam angle	≤ ±2.5 ° (SH4/*-*EI*)			
SAFETY PARAMETERS				
Type	4 (IEC 61496)			
PL	e (EN ISO 13849)			
PFHd	8.1 x 10-10			
INPUT/OUTPUT				
Output type			Totem-pole	
Output function			To be connected to SBCR03	
HMI/UI				
LED indicators	Yellow (power)		Yellow (alignment)	
ELECTRICAL DATA				
Supply voltage	10 ... 30 Vdc			
Maximum residual ripple	5%			
Maximum No-load absorption	25mA			
Maximum DC output voltage drop			2.5 V @ IL=50mA	
Maximum DC output voltage drop			70 mA	
MECHANICAL DATA				
Dimensions	M18x1 / L=98 mm			
Diameter / Dimensions	M18			
Housing material	PBT, Metal			
Active part material	Glass			
ENVIRONMENTAL DATA				
Operating Temperature	-20 ... 55 °C (without freeze)			
Mechanical Protection	IP67			
Storage temperature max.	-40 ... 75 °C			
Shocks and vibrations	IEC60068-2-6			
Humidity	15 ... 95 % no condensation			

TECHNICAL SPECIFICATIONS

	TH2/E-KIC	TH2/R-KIC
	SAFETY TYPE 4	
GENERAL DATA		
Operating principle	Emitter	Receiver
DETECTION CAPABILITIES		
Nominal sensing distance	0 ... 60 m	
Controlled height	Single-beam	
Thermal drift	≤ 10% Sr	
EMISSION DATA		
Emission	Red	
Effective beam angle	≤ ±5 ° (TH2/*-KIC)	
SAFETY PARAMETERS		
Type	2 (IEC 61496)	
PL	c (EN ISO 13849)	
PFHd	1 x 10 ⁻⁶	
INPUT/OUTPUT		
Output type		Totem-pole
HMI/UI		
LED indicators	Yellow (power)	Yellow (alignment)
ELECTRICAL DATA		
Supply voltage	10 ... 30 Vdc	
Maximum residual ripple	5%	
Maximum No-load absorption	25mA	
Maximum DC output voltage drop		2.5 V @ IL=50mA
Maximum DC output voltage drop		70 mA
MECHANICAL DATA		
Dimensions	M30x1.5 / L=100 mm	
Diameter / Dimensions	M30	
Housing material	Metal	
Active part material	Glass	
Optical location	Axial	
ENVIRONMENTAL DATA		
Operating Temperature	-20 ... 55 °C (without freeze)	
Mechanical Protection	IP67	
Storage temperature max.	-40 ... 75 °C	
Shocks and vibrations	IEC60068-2-6	
Humidity	15 ... 95 % no condensation	

TECHNICAL SPECIFICATIONS



	TH6/E-KIA	TH6/E-KIC	TH6/R-KIA	TH6/R-KIC
	SAFETY TYPE 4 			
GENERAL DATA				
Operating principle	Emitter		Receiver	
Control units to be used	SBCR03 Series		SBCR03 Series	
DETECTION CAPABILITIES				
Nominal sensing distance	0 ... 60 m			
Controlled height	Single-beam			
Thermal drift	≤ 10% Sr			
EMISSION DATA				
Emission	Red			
Effective beam angle	≤ ±2.5 ° (TH6/*-KI*)			
SAFETY PARAMETERS				
Type	4 (IEC 61496)			
Pl	e (EN ISO 13849)			
PFHd	8.1 x 10-10			
INPUT/OUTPUT				
Output type			Totem-pole	
Output function			To be connected to SBCR03	
HMI/UI				
LED indicators	Yellow (power)		Yellow (alignment)	
ELECTRICAL DATA				
Supply voltage	10 ... 30 Vdc			
Maximum residual ripple	5%			
Maximum No-load absorption	25mA			
Maximum DC output voltage drop			2.5 V @ IL=50mA	
Maximum DC output voltage drop			70 mA	
MECHANICAL DATA				
Dimensions	M30x1.5 / L=100 mm			
Diameter / Dimensions	M30			
Housing material	Metal			
Active part material	Glass			
Optical location	Axial			
ENVIRONMENTAL DATA				
Operating Temperature	-20 ... 55 °C (without freeze)			
Mechanical Protection	IP67			
Storage temperature max.	-40 ... 75 °C			
Shocks and vibrations	IEC60068-2-6			
Humidity	15 ... 95 % no condensation			

SH/TH AVAILABLE MODELS



SAFETY SENSORS

Diameter / Dimensions	Type	Operating principle	Nominal sensing distance	Housing material	Model
M18	2	Emitter	Red Emitter 0 ... 10 m	PBT	SH2/E-0EIC
					SH2/E-0KIC
					SH2/E-2EIC
				Metal	SH2/E-1EIC
					SH2/E-1KIC
					SH2/E-3EIC
		Receiver	Receiver 0 ... 10 m	PBT	SH2/R-0EIC
					SH2/R-0KIC
					SH2/R-2EIC
				Metal	SH2/R-1EIC
					SH2/R-1KIC
					SH2/R-3EIC
	4	Emitter	Red Emitter 0 ... 10 m	PBT	SH4/E-0EIA
					SH4/E-0KIA
					SH4/E-2EIA
					SH4/E-0EIC
					SH4/E-2EIC
				Metal	SH4/E-1EIA
					SH4/E-1KIA
					SH4/E-1EIC
					SH4/E-3EIC
		Receiver	Receiver 0 ... 10 m	PBT	SH4/R-0EIA
					SH4/R-0KIA
					SH4/R-2EIA
					SH4/R-0EIC
					SH4/R-2EIC
					SH4/R-1EIA
					SH4/R-1KIA
					SH4/R-1EIC
					SH4/R-3EIC
M30	2	Emitter	Red Emitter 0 ... 60 m	Metal	TH2/E-KIC
		Receiver	Receiver 0 ... 60 m		TH2/R-KIC
	4	Emitter	Red Emitter 0 ... 60 m		TH6/E-KIA
					TH6/E-KIC
		Receiver	Receiver 0 ... 60 m		TH6/R-KIA
					TH6/R-KIC


CONNECTIONS

SH*/E-****, TH*/E-***			
 MALE M12 3 pins SH /TH safety sensors	1	Brown	10...30 Vdc
	2		n.c.
	3	Blue	
	4	Black	Test
SH*/R-****, TH*/R-***			
 MALE M12 3 pins SH /TH safety sensors	1	Brown	10...30 Vdc
	2		n.c.
	3	Blue	
	4	Black	Output

MECHANICAL DRAWINGS

SH*/*-0E**	SH*/*-1E**
 (mm)	 (mm)

SH*/*-0K**



(mm)



Models

SH*/*-0K**


A

LED

SH*/*-2E**



(mm)



SH/TH ACCESSORIES TO BE ORDERED SEPARATELY

SAFETY SENSORS

	Model	Description	Article code
Cables	CD12M/0B-050C5	Connect.M12-F,4 poles-5m,PUR,90°	CD12M/0B-050C5
	CD12M/0B-070A1	Connect.M12-F,4 poles-7m,PVC,Axial	CD12M/0B-070A1
	CD12M/0B-070C1	Connect.M12-F,4 poles-7m,PVC,90°	CD12M/0B-070C1
	CD12M/0B-100A1	Connect.M12-F,4 poles-10m,PVC,Axial	CD12M/0B-100A1
	CD12M/0B-100A5	Connect.M12-F,4 poles-10m,PUR,Axial	CD12M/0B-100A5
	CD12M/0B-100C1	Connect.M12-F,4 poles-10m,PVC,90°	CD12M/0B-100C1
	CD12M/0B-100C5	Connect.M12-F,4 poles-10m,PUR,90°	CD12M/0B-100C5
	CD12M/0B-150A1	Connect.M12-F,4 poles-15m,PVC,Axial	CD12M/0B-150A1
	CD12M/0B-150C1	Connect.M12-F,4 poles-15m,PVC,90°	CD12M/0B-150C1
	CD12M/0B-200A1	Connect.M12-F,4 poles-20m,PVC,Axial	CD12M/0B-200A1
	CD12M/0B-200C1	Connect.M12-F,4 poles-20m,PVC,90°	CD12M/0B-200C1
	CD12M/0B-050B1	Connector Male M12 Axial 4 poles cable PVC 5 m	CD12M/0B-050B1
	CD12M/0B-100B1	Connector Male M12 Axial 4 poles cable PVC 10 m	CD12M/0B-100B1
	CD12M/AA-020A1	Connect.M12-F,3 poles-2m,PVC,Axial	CD12M/AA-020A1
	CD12M/AA-020C1	Connect.M12-F,3 poles-2m,PVC,90°	CD12M/AA-020C1
	CD12M/AA-050A1	Connect.M12-F,3 poles-5m,PVC,Axial	CD12M/AA-050A1
	CD12M/AA-050C1	Connect.M12-F,3 poles-5m,PVC,90°	CD12M/AA-050C1
	CD12M/AA-070A1	Connect.M12-F,3 poles-7m,PVC,Axial	CD12M/AA-070A1
	CD12M/AA-070C1	Connect.M12-F,3 poles-7m,PVC,90°	CD12M/AA-070C1
	CD12M/AA-100A1	Connect.M12-F,3 poles-10m,PVC,Axial	CD12M/AA-100A1
	CD12M/AA-100C1	Connect.M12-F,3 poles-10m,PVC,90°	CD12M/AA-100C1
	CD12M/AA-150A1	Connect.M12-F,3 poles-15m,PVC,Axial	CD12M/AA-150A1
	CD12M/AA-150C1	Connect.M12-F,3 poles-15m,PVC,90°	CD12M/AA-150C1
	CD12M/AA-200C1	Connect.M12-F,3 poles-20m,PVC,90°	CD12M/AA-200C1
	CD12M/0B-020A1	Connect.M12-F,4 poles-2m,PVC,Axial	CD12M/0B-020A1
	CD12M/0B-020A5	Connect.M12-F,4 poles-2m,PUR,Axial	CD12M/0B-020A5
	CD12M/0B-020C1	Connect.M12-F,4 poles-2m,PVC,90°	CD12M/0B-020C1
	CD12M/0B-020C5	Connect.M12-F,4 poles-2m,PUR,90°	CD12M/0B-020C5
	CD12M/0B-050A1	Connect.M12-F,4 poles-5m,PVC,Axial	CD12M/0B-050A1
	CD12M/0B-050A5	Connect.M12-F,4 poles-5m,PUR,Axial	CD12M/0B-050A5
	CD12M/0B-050C1	Connect.M12-F,4 poles-5m,PVC,90°	CD12M/0B-050C1
Mounting brackets	ST 18-A	Bracket M18 axial	ST 18-A
	ST 18-A7W	Bracket M18 axial AISI316L	ST 18-A7W
	ST 18-C	Bracket M18 90°	ST 18-C
	ST 18-C7W	Bracket M18 90° AISI316L	ST 18-C7W
	ST 18-V	Vertical fixing bracket	ST 18-V

The company endeavors to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products. Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.