



SG4-H

957901710

SG4-H14-045-OO-X-B

**STAINLESS STEEL TYPE 4 SAFETY LIGHT CURTAIN FOR
PHARMA INDUSTRY**

OVERVIEW

- Stainless steel housing
- Hygienic design
- No need for additional protection tubes
- IP69K full protection
- Housing: AISI316L stainless steel with roughness under 0.8 micron
- Window: Optical glass
- Rounded surfaces with no gaps or sharp edges
- No labels: All information laser marked
- Maximum safety: Type 4, finger resolution
- Three protection heights: 150, 300 and 450 mm
- 50 x 30 mm profile
- 4 LEDs and 7-segment display alignment aiding

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 6 m
--------------------------	-------------

Resolution	14mm
------------	------

controlled height	450 mm
-------------------	--------

number of rays	48
----------------	----

Sensitivity adjustment	n/a
Effective Aperture Angle	$\leq \pm 2,5^\circ$

Application

Function Principle	Emitter + Receiver
Available functions	Automatic Restart, IP69K Hygienic Design
Description	Hygienic design bottom mount
Functions	Finger protection res. 14 mm

Safety parameters

Type	Type 4 safety light curtain (A)
SIL	3
SILCL	3
PL	e
MTTFd	444 years
Dcavg	98,80%
SFF	99,30%

Outputs

Output type	2 x PNP-NO (OSSD safety output)
Response time	18 ms

Electrical data

Operating Voltage

24 Vdc $\pm$ 20%

Load current

$\leq$ 500mA each output

Emission

Infrared LED (850 nm wavelength)

Interference to external light

According to IEC 61496-2

Power Consumption - Receiver

$\leq$ 3,5W (no load)

Power Consumption - Emitter

$\leq$ 2,5W

Cabel Length (Power Supply/Output)

$\leq$ 50m

Mechanical data

Dimensions

30x53x590

Material

Stainless steel AISI 316L / Glass

Connections

M12-4 poles (emitter) M12-5 poles (receiver)

Storage temperature

-25...+ 70°C

Vibrations

Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)

Shocks

16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

EMC compatibility

According to 2014/30/EU Directive

Generical Data

Dimensions	33x53x590,6 mm
Operating Temperature	-10...+55°C
Humidity	15 ... 95 % (no condensation)
Mechanical Protection	IP65, IP69K
UNASSIGNED	
Disegno 2D PDF	2,64E-09

**Datasensing
S.r.l.**
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
10:50:33