



SG4-H

957902330

SG4-H14-015-00-X-G

STAINLESS STEEL TYPE 4 SAFETY LIGHT CURTAIN FOR PHARMA INDUSTRY

OVERVIEW

- Stainless steel housing
- Hygienic design
- No need for additional protection tubes
- IP69K full protection
- Housing: AISI316L stainless steel with roughness under 0.8 micron
- Window: Optical glass
- Rounded surfaces with no gaps or sharp edges
- No labels: All information laser marked
- Maximum safety: Type 4, finger resolution
- Three protection heights: 150, 300 and 450 mm
- 50 x 30 mm profile
- 4 LEDs and 7-segment display alignment aiding

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 6 m
--------------------------	-------------

Resolution	14mm
------------	------

controlled height	150 mm
-------------------	--------

number of rays	16
----------------	----

Sensitivity adjustment	n/a
Effective Aperture Angle	$\leq \pm 2,5^\circ$

Application

Function Principle	Emitter + Receiver
Available functions	Automatic Restart, IP69K Hygienic Design
Description	Hygienic design top-bottom mount
Functions	Finger protection res. 14 mm

Safety parameters

Type	Type 4 safety light curtain (A)
SIL	3
SILCL	3
PL	e
PFHd	2,64E-09
Dcavg	98,80%
MTTFd	444 years
SFF	99,30%

Outputs

Output type	2 x PNP-NO (OSSD safety output)
-------------	---------------------------------

Response time	11 ms
---------------	-------

Electrical data

Operating Voltage	24 Vdc \pm 20%
-------------------	------------------

Load current	\leq 500mA each output
--------------	--------------------------

Emission	Infrared LED (850 nm wavelength)
----------	----------------------------------

Interference to external light	According to IEC 61496-2
--------------------------------	--------------------------

Power Consumption - Receiver	\leq 3,5W (no load)
------------------------------	-----------------------

Power Consumption - Emitter	\leq 2,5W
-----------------------------	-------------

Cabel Length (Power Supply/Output)	\leq 50m
------------------------------------	------------

Mechanical data

Dimensions	30x53x302
------------	-----------

Connections	M12-4 poles (emitter) M12-5 poles (receiver)
-------------	--

Storage temperature	-25...+ 70°C
---------------------	--------------

Material	Stainless steel AISI 316L / Glass
----------	-----------------------------------

Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
------------	---

Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)
--------	--

Test/Approvals

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Generical Data

Dimensions	33x53x302,3 mm
Operating Temperature	-10...+55°C
Humidity	15 ... 95 % (no condensation)
Mechanical Protection	IP65, IP69K

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
08/05/2026
17:05:27