



SLIM

957910050

SL4-14-0360-E

SLIM SAFETY LIGHT CURTAIN FOR FINGER AND HAND PROTECTION

OVERVIEW

- Highest mechanical flexibility for a perfect fit into machine structures
- Simple commissioning and maintenance
- High functional performance
- SLIM profile: 15 x 32 mm
- Pigtail cable with 5-pole M12 connectors
- Same cable for Emitter and Receiver
- No Dead Zone
- 14, 24 and 34 mm resolution
- 34 different protection lengths, with 30 mm modularity
- 3 different brackets shapes
- Cascadable up to 3 units
- Auto/Manual restart and EDM function configuration by wiring
- LED display messages diagnosis

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 6 m
--------------------------	-------------

Resolution	14mm
------------	------

controlled height	360 mm
-------------------	--------

number of rays	36
----------------	----

Sensitivity adjustment	n/a
Effective Aperture Angle	$\leq \pm 2,5^\circ$

Application

Function Principle	Emitter + Receiver
Available functions	Manual/Automatic Restart, EDM
Description	SLIM no-dead-zone cascable
Functions	Finger protection res. 14 mm

Safety parameters

Type	Type 4 safety light curtain (A/M)
SIL	3
SILCL	3
PL	e
PFHd	1,04E -08
MTTFd	444 years

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
Response time	9 ms
Response Time (Master + Slave)	18 ms

Response Time (Master + 2 Slave)	20 ms
----------------------------------	-------

Electrical data

Operating Voltage	24 Vdc \pm 20%
-------------------	------------------

Load current	\leq 500mA each output
--------------	--------------------------

Emission	Infrared LED (850 nm wavelength)
----------	----------------------------------

Interference to external light	According to IEC 61496-2
--------------------------------	--------------------------

Power Consumption - Receiver	\leq 4,2W (no load)
------------------------------	-----------------------

Power Consumption - Emitter	\leq 1,6W
-----------------------------	-------------

Cabel Length (Power Supply/Output)	\leq 20m
------------------------------------	------------

Cable Length for Master Slave Interconnections	\leq 1m (Master-Slave Cable)
--	--------------------------------

Mechanical data

Dimensions	15x33x360
------------	-----------

Connections	M12-5 poles pig-tail (emitter) M12-5 poles pig-tail (receiver)
-------------	--

Storage temperature	-25...+ 70°C
---------------------	--------------

Material	Metal - Aluminium / PMMA / Painted Zamak
----------	--

Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
------------	---

Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)
--------	--

Test/Approvals

EMC compatibility

According to 2014/30/EU Directive

Accessories

Supplied Accessories

C-shaped Brackets (included): 2 pcs kit + O-shaped Brackets (included): 4 pcs kit

Generical Data

Dimensions

15,4x32,6x360 mm

Operating Temperature

-10...+55°C

Humidity

15 ... 95 % (no condensation)

Mechanical Protection

IP65

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
23/04/2026
17:45:57