



# SG2 Base

957801110

SG2-30-180-OO-X

TYPE 2 SAFETY LIGHT CURTAIN WITH BASIC  
FUNCTIONALITY

## OVERVIEW

- High reliability
- Easy installation and alignment
- Cost effective Finger, hand, arm detection with basic functions
- 90 mm version for presence detection
- Up to 19 m operating distance
- Compact dimensions (32.3 x 36.9 mm section)
- Anti-interference coding
- IP65 Protection; IP69K with optional tube
- Unshielded cables
- Rotating and anti-vibration brackets

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	0,2 ... 19 m
Resolution	30mm
controlled height	1800 mm
number of rays	96
Sensitivity adjustment	n/a

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

### Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Automatic Restart
---------------------	-------------------

Description	Compact standard
-------------	------------------

Functions	Hand protection res. 30 mm
-----------	----------------------------

### Safety parameters

Type	Type 2 safety light curtain (A)
------	---------------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	c
----	---

PFHd	1,04E-08
------	----------

Dcavg	97,50%
-------	--------

MTTFd	273 years
-------	-----------

SFF	98,40%
-----	--------

### Outputs

Output type	2 x PNP-NO (OSSD safety output)
-------------	---------------------------------

Response time	24 ms
---------------	-------

## Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
Load current	$\leq$ 500mA each output
Emission	Infrared LED (850 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	$\leq$ 3W (no load)
Power Consumption - Emitter	$\leq$ 2W
Capacitive Load	$\geq$ 2,2 $\mu$ F
Cabel Length (Power Supply/Output)	$\leq$ 50m

## Mechanical data

Dimensions	33x37x1883
Connections	M12-4 poles (emitter) M12-5 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC MAKROLON
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

## Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility

According to 2014/30/EU Directive

#### Accessories

Supplied Accessories

Standard "L" Mounting Brackets: 6 pcs kit

#### Generical Data

Dimensions

32,3x36,9x1883,2 mm

Operating Temperature

-10...+55°C

Humidity

15 ... 95 % (no condensation)

Mechanical Protection

IP65

### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
17/04/2026  
05:34:58