



SG2 Muting

957801720

SG2-30-060-OO-W
TYPE 2 SAFETY LIGHT CURTAIN FOR HAND DETECTION
WITH MUTING

OVERVIEW

- No dead zone
- Pigtail cable with M12 connector
- Up to 20m operating range and 1800m protected height
- Compact dimensions (35 x 41 mm section)
- Anti-interference coding
- Integrated Muting function
- Configurable with Pushbuttons

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 20 m
Resolution	30mm
controlled height	600 mm
number of rays	32
Sensitivity adjustment	Teach-in
Effective Aperture Angle	$\leq \pm 5^\circ$

--

Application

Function Principle	Emitter + Receiver
Available functions	Manual/Automatic Restart, EDM, Range Reduction (on TX), Muting, Override
Description	Compact no-dead-zone
Functions	Hand protection res. 30 mm muting

Safety parameters

Type	Type 2 safety light curtain (A/M)
SIL	1
SILCL	1
PL	c
MTTFd	273 years
Dcavg	97,50%
SFF	98,40%

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
Response time	14,8 ms

Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
-------------------	------------------

Load current	≤ 500mA each output
Emission	Infrared LED (950 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	≤ 5W (no load)
Power Consumption - Emitter	≤ 3W
Capacitive Load	≥ 2,2μF
Cabel Length (Power Supply/Output)	≤ 50m

Mechanical data

Dimensions	35x41x606
Material	Painted aluminum / PMMA / PBT Valox 508 / PC LEXAN
Connections	M12-5 poles pig-tail (emitter) M12-12 poles + M12-5poles pig-tails (receiver)
Storage temperature	-25...+ 70°C
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
EMC compatibility	According to 2014/30/EU Directive

Accessories

||
||
||

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

Generical Data

Dimensions	35x40,75x606,3 mm
------------	-------------------

Operating Temperature	0...+50°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

UNASSIGNED

Disegno 2D PDF	1,04E-08
----------------	----------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
06:58:22