



SG2 Extended

957801340

SG2-30-015-OO-E-C

TYPE 2 SAFETY LIGHT CURTAIN WITH STANDARD
FUNCTIONALITY

OVERVIEW

- High reliability
- Easy installation and alignment
- Cost effective Finger, hand, arm detection with standard functions
- 90 mm version for presence detection
- Up to 19 m operating distance
- Compact dimensions (32.3 x 36.9 mm section)
- Anti-interference coding
- IP65 Protection; IP69K with optional tube
- Unshielded cables
- Rotating and anti-vibration brackets

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 19 m
Resolution	30mm
controlled height	150 mm
number of rays	8
Sensitivity adjustment	n/a

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM, Range Reduction (on TX)
---------------------	--

Description	Compact standard
-------------	------------------

Functions	Hand protection res. 30 mm
-----------	----------------------------

Safety parameters

Type	Type 2 safety light curtain (A/M)
------	-----------------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	c
----	---

PFHd	1,04E-08
------	----------

Dcavg	97,50%
-------	--------

MTTFd	273 years
-------	-----------

SFF	98,40%
-----	--------

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	8 ms
---------------	------

Electrical data

Operating Voltage	24 Vdc \pm 20%
Load current	\leq 500mA each output
Emission	Infrared LED (850 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	\leq 3W (no load)
Power Consumption - Emitter	\leq 2W
Capacitive Load	\geq 2,2 μ F
Cabel Length (Power Supply/Output)	\leq 50m

Mechanical data

Dimensions	33x37x233
Connections	M12-4 poles (emitter) M12-8 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC MAKROLON
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Accessories

Supplied Accessories	Rotating Brackets: 4 pcs kit
----------------------	------------------------------

Generical Data

Dimensions	32,3x36,9x233,3 mm
------------	--------------------

Operating Temperature	-10...+55°C
-----------------------	-------------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
19/04/2026
23:15:35