



# SG4 Base

957901000

SG4-14-015-OO-E

TYPE 4 SAFETY LIGHT CURTAIN WITH BASIC  
FUNCTIONALITY

## OVERVIEW

- High reliability
- Easy installation and alignment
- Cost effective Finger, hand detection with basic functions
- Up to 19 m operating distance
- Compact dimensions (32.3 x 36.9 mm section)
- Anti-interference coding
- IP65 Protection; IP69K with optional tube
- Unshielded cables
- Rotating and anti-vibration brackets

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	0,2 ... 6 m
Resolution	14mm
controlled height	150 mm
number of rays	16
Sensitivity adjustment	n/a

Effective Aperture Angle	$\leq \pm 2,5^\circ$
--------------------------	----------------------

#### Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM
---------------------	-------------------------------

Description	Compact standard
-------------	------------------

Functions	Finger protection res. 14 mm
-----------	------------------------------

#### Safety parameters

Type	Type 4 safety light curtain (A/M)
------	-----------------------------------

SIL	3
-----	---

SILCL	3
-------	---

PL	e
----	---

PFHd	2,64E-09
------	----------

Dcavg	98,80%
-------	--------

MTTFd	444 years
-------	-----------

SFF	99,30%
-----	--------

#### Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	9 ms
---------------	------

## Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
Load current	$\leq$ 500mA each output
Emission	Infrared LED (850 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	$\leq$ 3,5W (no load)
Power Consumption - Emitter	$\leq$ 2,5W
Cabel Length (Power Supply/Output)	$\leq$ 50m

## Mechanical data

Dimensions	33x37x233
Connections	M12-5 poles (emitter) M12-5 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC MAKROLON
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

## Test/Approvals

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

## Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

## Generical Data

Dimensions	32,3x36,9x233,3 mm
------------	--------------------

Operating Temperature	-10...+55°C
-----------------------	-------------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
05/04/2026  
16:57:08