



SG4 Base

957901010

SG4-14-030-OO-E

TYPE 4 SAFETY LIGHT CURTAIN WITH BASIC
FUNCTIONALITY

OVERVIEW

- High reliability
- Easy installation and alignment
- Cost effective Finger, hand detection with basic functions
- Up to 19 m operating distance
- Compact dimensions (32.3 x 36.9 mm section)
- Anti-interference coding
- IP65 Protection; IP69K with optional tube
- Unshielded cables
- Rotating and anti-vibration brackets

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,2 ... 6 m
Resolution	14mm
controlled height	300 mm
number of rays	32
Sensitivity adjustment	n/a

Effective Aperture Angle	$\leq \pm 2,5^\circ$
--------------------------	----------------------

Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM
---------------------	-------------------------------

Description	Compact standard
-------------	------------------

Functions	Finger protection res. 14 mm
-----------	------------------------------

Safety parameters

Type	Type 4 safety light curtain (A/M)
------	-----------------------------------

SIL	3
-----	---

SILCL	3
-------	---

PL	e
----	---

PFHd	2,64E-09
------	----------

Dcavg	98,80%
-------	--------

MTTFd	444 years
-------	-----------

SFF	99,30%
-----	--------

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	12,7 ms
---------------	---------

Electrical data

Operating Voltage	24 Vdc \pm 20%
Load current	\leq 500mA each output
Emission	Infrared LED (850 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	\leq 3,5W (no load)
Power Consumption - Emitter	\leq 2,5W
Cabel Length (Power Supply/Output)	\leq 50m

Mechanical data

Dimensions	33x37x383
Connections	M12-5 poles (emitter) M12-5 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC MAKROLON
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

Generical Data

Dimensions	32,3x36,9x383,2 mm
------------	--------------------

Operating Temperature	-10...+55°C
-----------------------	-------------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
04/05/2026
17:18:12