



SG BODY BIG BASE / MUTING

957851250

SG2-B3-080-00-E

ROBUST TYPE 4 SAFETY LIGHT GRID FOR BODY AND ARM
DETECTION

OVERVIEW

- Robust housing for harsh environments
- Long operating range for perimeter control
- Rapid solution for access control with muting
- Easy installation and alignment
- 2, 3, 4 beams for body protection
- 40 mm resolution for arm protection and presence detection
- Controlled heights 500, 800, 900 and 1200 mm
- Long operating distance: up to 60 m
- Simple configuration through DIP switches
- Integrated muting lamp (only muting models)
- Anti-interference coding
- External muting enable signal
- Edged or triggered muting dependent override

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,5 ... 60 m
Resolution	400mm
controlled height	800 mm
number of rays	3

Sensitivity adjustment	n/a
------------------------	-----

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM
---------------------	-------------------------------

Description	Big for harsh environment
-------------	---------------------------

Functions	Body protection 3 beams
-----------	-------------------------

Safety parameters

Type	Type 2 safety light curtain (A/M)
------	-----------------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	c
----	---

MTTFd	317 years
-------	-----------

Dcavg	96,70%
-------	--------

SFF	98,00%
-----	--------

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	13 ms
---------------	-------

Electrical data

Operating Voltage	24 Vdc \pm 20%
Load current	\leq 500mA each output
Emission	Infrared LED (950 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	\leq 4W (no load)
Power Consumption - Emitter	\leq 2,5W
Capacitive Load	\geq 2,2 μ F
Cabel Length (Power Supply/Output)	\leq 70m

Mechanical data

Dimensions	52x60x906
Material	Painted aluminum / PMMA / PBT Valox 508
Connections	M12-5 poles pig-tail (emitter) M12-8 poles pig-tail (receiver)
Storage temperature	-25...+ 70°C
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Generical Data

Dimensions	52x56,9x906,35 mm
------------	-------------------

Operating Temperature	0...+55°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

UNASSIGNED

Disegno 2D PDF	1,19E-08
----------------	----------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
13/06/2026
04:44:59