

# SG BODY COMPACT BASE / MUTING



957851060

SG4-S4-090-PP-E

COMPACT TYPE 4 SAFETY LIGHT GRID FOR BODY  
DETECTION

## OVERVIEW

- Body access detection
- Perimeter control
- Rapid solution for access control with muting
- Easy installation and alignment
- L and T muting models provided with Retroreflective Muting Arms
- Two, three or four beams for body protection
- Controlled heights of 500, 800, 900 and 1200 mm
- Long operating distance: up to 50 m
- Simple configuration through DIP switches
- Integrated muting lamp (only on muting models)

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	0,5 ... 50 m
Resolution	300mm
controlled height	900 mm
number of rays	4
Sensitivity adjustment	Dip-switch

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

#### Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM
---------------------	-------------------------------

Description	Compact standard
-------------	------------------

Functions	Body protection 4 beams
-----------	-------------------------

#### Safety parameters

Type	Type 4 safety light curtain (A/M)
------	-----------------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	e
----	---

PFHd	2,62E-09
------	----------

Dcavg	98,90%
-------	--------

MTTFd	384 years
-------	-----------

SFF	99.38%
-----	--------

#### Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	16 ms
---------------	-------

## Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
Load current	$\leq$ 500mA each output
Emission	Infrared LED (880 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	$\leq$ 2W (no load)
Power Consumption - Emitter	$\leq$ 0,9W
Equivalent Resistive Load	$\geq$ 56 $\Omega$
Capacitive Load	$\leq$ 65nF
Cabel Length (Power Supply/Output)	$\leq$ 50m

## Mechanical data

Dimensions	35x41x1063
Connections	M12-4 poles (emitter) M12-8 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC Lexan 943A
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

## Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

#### Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

#### Generical Data

Dimensions	35x41,2x1064 mm
------------	-----------------

Operating Temperature	0...+55°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
04/04/2026  
16:15:14