

SG BODY COMPACT BASE / MUTING



957851070

SG4-S4-120-PP-E

COMPACT TYPE 4 SAFETY LIGHT GRID FOR BODY
DETECTION

OVERVIEW

- Body access detection
- Perimeter control
- Rapid solution for access control with muting
- Easy installation and alignment
- L and T muting models provided with Retroreflective Muting Arms
- Two, three or four beams for body protection
- Controlled heights of 500, 800, 900 and 1200 mm
- Long operating distance: up to 50 m
- Simple configuration through DIP switches
- Integrated muting lamp (only on muting models)

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,5 ... 50 m
Resolution	400mm
controlled height	1200 mm
number of rays	4
Sensitivity adjustment	Dip-switch

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Manual/Automatic Restart, EDM
---------------------	-------------------------------

Description	Compact standard
-------------	------------------

Functions	Body protection 4 beams
-----------	-------------------------

Safety parameters

Type	Type 4 safety light curtain (A/M)
------	-----------------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	e
----	---

PFHd	2,62E-09
------	----------

Dcavg	98,90%
-------	--------

MTTFd	384 years
-------	-----------

SFF	99.38%
-----	--------

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
-------------	--

Response time	16 ms
---------------	-------

Electrical data

Operating Voltage	24 Vdc \pm 20%
Load current	\leq 500mA each output
Emission	Infrared LED (880 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	\leq 2W (no load)
Power Consumption - Emitter	\leq 0,9W
Equivalent Resistive Load	\geq 56 Ω
Capacitive Load	\leq 65nF
Cabel Length (Power Supply/Output)	\leq 50m

Mechanical data

Dimensions	35x41x1363
Connections	M12-4 poles (emitter) M12-8 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC Lexan 943A
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 6 pcs kit
----------------------	---

Generical Data

Dimensions	35x41,2x1364 mm
------------	-----------------

Operating Temperature	0...+55°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
07/04/2026
07:21:53