

SG BODY COMPACT BASE / MUTING



957851090

SG2-S3-080-PP-W

**COMPACT TYPE 4 SAFETY LIGHT GRID FOR BODY
DETECTION**

OVERVIEW

- Body access detection
- Perimeter control
- Rapid solution for access control with muting
- Easy installation and alignment
- L and T muting models provided with Retroreflective Muting Arms
- Two, three or four beams for body protection
- Controlled heights of 500, 800, 900 and 1200 mm
- Long operating distance: up to 50 m
- Simple configuration through DIP switches
- Integrated muting lamp (only on muting models)

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,5 ... 50 m
--------------------------	--------------

Resolution	400mm
------------	-------

controlled height	800 mm
-------------------	--------

number of rays	3
----------------	---

Sensitivity adjustment	Dip-switch
------------------------	------------

Effective Aperture Angle	$\leq \pm 5^\circ$
--------------------------	--------------------

Application

Function Principle	Emitter + Receiver
Available functions	Manual/Automatic Restart, EDM, L/T Muting, Override
Description	Compact standard
Functions	Body protection 3 beams muting

Safety parameters

Type	Type 2 safety light curtain (A/M)
SIL	1
SILCL	1
PL	e
PFHd	1,00E-08
Dcavg	97,00%
MTTFd	337 years
SFF	98.14%

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
Response time	15 ms

Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
Load current	$\leq$ 500mA each output
Emission	Infrared LED (880 nm wavelength)
Interference to external light	According to IEC 61496-2
Power Consumption - Receiver	$\leq$ 2,2W (no load)
Power Consumption - Emitter	$\leq$ 0,9W
Equivalent Resistive Load	$\geq$ 56 Ω
Capacitive Load	$\leq$ 65nF
Cabel Length (Power Supply/Output)	$\leq$ 50m

Mechanical data

Dimensions	35x41x962
Connections	M12-4 poles + M12-5 poles (emitter) M12-8 poles + M12-5 poles (receiver)
Storage temperature	-25...+ 70°C
Material	Painted aluminum / PMMA / PC Lexan 943A
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

Generical Data

Dimensions	35x41,2x964 mm
------------	----------------

Operating Temperature	0...+55°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
05/07/2025
12:44:08