

SG BODY COMPACT BASE / MUTING



957851620

SG4-S4-090-PP-X

COMPACT TYPE 4 SAFETY LIGHT GRID FOR BODY
DETECTION

OVERVIEW

- Body access detection
- Perimeter control
- Rapid solution for access control with muting
- Easy installation and alignment
- L and T muting models provided with Retroreflective Muting Arms
- Two, three or four beams for body protection
- Controlled heights of 500, 800, 900 and 1200 mm
- Long operating distance: up to 50 m
- Simple configuration through DIP switches
- Integrated muting lamp (only on muting models)

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,5 ... 50 m
Resolution	300mm
controlled height	900 mm
number of rays	4
Sensitivity adjustment	n/a

Effective Aperture Angle	$\leq \pm 2,5^{\circ}$
--------------------------	------------------------

Application

Function Principle	Emitter + Receiver
Available functions	Automatic Restart
Description	Compact standard
Functions	Body protection 4 beams

Safety parameters

Type	Type 4 safety light curtain (A)
SIL	3
SILCL	3
PL	e
PFHd	2,62E-09
Dcavg	98,90%
MTTFd	384 years
SFF	98.14%

Outputs

Output type	2 x PNP-NO (OSSD safety output)
Response time	16 ms

Electrical data

Operating Voltage

24 Vdc $\pm$ 20%

Load current

$\leq$ 500mA each output

Emission

Infrared LED (880 nm wavelength)

Interference to external light

According to IEC 61496-2

Power Consumption - Receiver

$\leq$ 2W (no load)

Power Consumption - Emitter

$\leq$ 0,9W

Equivalent Resistive Load

$\geq$ 56 Ω

Capacitive Load

$\leq$ 65nF

Cabel Length (Power Supply/Output)

$\leq$ 50m

Mechanical data

Dimensions

35x41x1063

Connections

M12-4 poles (emitter) M12-5 poles (receiver)

Storage temperature

-25...+ 70°C

Material

Painted aluminum / PMMA / PC Lexan 943A

Vibrations

Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)

Shocks

16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus, TÜV
-----------	----------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

Generical Data

Dimensions	35x41,2x1064 mm
------------	-----------------

Operating Temperature	0...+55°C
-----------------------	-----------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
27/01/2026
03:54:49