



SH4 Active-Passive

957920240

SH4-3-0800-A-AP-12-5

TYPE 4 ACTIVE/PASSIVE SAFETY LIGHT CURTAIN FULLY
WIRELESS PROGRAMMABLE

OVERVIEW

- Type 4 safety light curtains with active/passive operating principle
- Passive side doesn't need to be wired
- Body protection with 500, 800, 900, 1200 mm controlled height
- Up to 8 m operating range (depending on model)
- Basic functions: alignment, automatic restart
- Standard functions: manual restart, EDM
- Standard Muting functions: 2-signals mono and bidirectional muting, override
- Advanced functions: partial muting, dynamic partial muting, 4-signals muting
- Innovative wireless monitoring and configuration system
- Compact profile (35 x 40 mm), common to all SH4 line
- Installation eased by LEDs indications of beam intensity
- IP67 Protection
- -30 ... +55 °C Operating temperature
- Complete couple and angular bracket included in the package
- Anti-interference codes
- Integrated LED muting indication
- Muting accessories available with prewired and preinstalled muting sensors
- Pigtails with M12 connectors with standard not shielded cables

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0.5 ... 8 m
--------------------------	-------------

Resolution	400 mm
------------	--------

controlled height	800 mm
number of rays	3
Effective Aperture Angle	$\leq \pm 2.5^\circ$

Application

Function Principle	Active Side and Retroreflective Passive Side
Available functions	Manual/Automatic Restart, EDM, L/T 2-signals Muting, T 4-signals Muting, Partial Muting, Muting Filter, Override, Wi-fi programmability
Description	Compact no-dead-zone ADVANCED Wi-Fi Programmable
Muting lamp output	Incandescent lamp or LED
Functions	Body protection 3 beams

Safety parameters

Type	Type 4 safety light curtain (A/M)
SIL	3
SILCL	3
PFHd	2,62E-08
PL	e
MTTFd	43 years
SFF	99,50%

Outputs

Output type	2 x PNP-NO (OSSD safety output) with EDM
Response time	15 ms

Electrical data

Operating Voltage	24 Vdc $\pm$ 20%
Power consumption	Active unit $\leq$ 2W (no load)
Load current	$\leq$ 250mA each output
Emission	Infrared LED (850 nm wavelength)
Interference to external light	According to IEC 61496-2
Capacitive Load	$\leq$ 1 μ F
Cabel Length (Power Supply/Output)	$\leq$ 30 m

Mechanical data

Material	Painted aluminum / MAKROLON AR 7099 Clear PC / PBT
Connections	M12-12 poles + M12-5 poles pigtails (active unit)
Storage temperature	-30 ...+70 °C
Vibrations	10 mm / 3 g, 5 ... 150 Hz frequency (EN 60068-2-6 / Class 3M7 IEC TR 60721-4-3)
Shocks	25 g x 6 ms x 600 (EN 60068-2-27 / Class 3M7 IEC TR 60721-4-3)

Test/Approvals

Approvals	CE, cULus, TÜV, UKCA
-----------	----------------------

EMC compatibility	According to 2014/30/EU Directive
-------------------	-----------------------------------

Shocks and vibrations	10 mm / 3g, 5 to 150 Hz frequency (EN 60068-2-6 / Class 3M7 IEC TR 60721-4-3); 25g x 6 ms x 600 (EN 60068-2-27 / Class 3M7 IEC TR 60721-4-3)
-----------------------	--

Accessories

Supplied Accessories	Standard "L" Mounting Brackets: 4 pcs kit
----------------------	---

Accessories to be ordered separately	Top-bottom rotating mounting bracket ST-K4ROT-SH
--------------------------------------	--

Generical Data

Dimensions	35x40x1026 mm
------------	---------------

Operating Temperature	-30...+55°C
-----------------------	-------------

Humidity	15 ... 95 % (no condensation)
----------	-------------------------------

Mechanical Protection	IP65, IP 67 (EN 60529)
-----------------------	------------------------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
05:43:40