



SH/TH

SH2/E-0KIC

Safety,M18,Emitter,M12 90°,Type 2
PHOTOCELLS TYPE 2 AND TYPE 4

OVERVIEW

- M18 Models 10 m (axial optic) and 5 m (radial optic) operating distance
- M30 models 60 m operating distance
- EN50100 Category 2 and Category 4 compliant
- LED indicators
- Plastic and Metal Housing
- Inputs and Outputs IEC61131-2 compliant and adaptable with any safety module
- To be used together with a Category 2 or Category 4 safety control unit to obtain a safety system EN ISO 13849 compliant



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	10m (ExG=4)
--------------------------	-------------

Thermal drift of Sr	≤ 10%
---------------------	-------

Resolution	Single-beam
------------	-------------

controlled height	Single-beam
-------------------	-------------

Effective Aperture Angle	Typical ±1,8°
--------------------------	---------------

Application

Function Principle	Emitter
--------------------	---------

Notes	not working with SBCR03 control unit. To be used with external safety control unit with automatic optics test function
-------	--

Description	M18 Type 2 Safety Photocell Emitter
-------------	-------------------------------------

Safety parameters

Type	Type 2 safety photocell
------	-------------------------

SIL	1
-----	---

SILCL	1
-------	---

PL	c
----	---

MTTFd	20 years
-------	----------

Electrical data

Operating Voltage	10 ... 30 Vdc
-------------------	---------------

No-Load supply current	≤ 25mA
------------------------	--------

Max ripple content	≤ 5 Vpp
--------------------	---------

LED indicators	Yellow (power)
----------------	----------------

Emission	Red
----------	-----

Test levels	<5V emission inactive >15V emission active
-------------	--

Mechanical data

Dimensions	M18
------------	-----

Housing material	PBT
------------------	-----

Connections	M12 plug
-------------	----------

Active Head Material	Glass
----------------------	-------

Operating temperature	-20°C ... +55°C
-----------------------	-----------------

Storage temperature	-40°C ... +75°C
---------------------	-----------------

Humidity	15% ... 95%
----------	-------------

Test/Approvals

Approvals	CE, TÜV
-----------	---------

Shocks and vibrations	10g - 16ms (according to IEC600068-2-29) 10Hz...55Hz - 1 oct/min - 0,35mm (according to 60068-2-6)
-----------------------	--

Degree of protection	IP67
----------------------	------

Accessories

Supplied Accessories	2 x nuts
----------------------	----------

Generical Data

Dimensions	M18
------------	-----

Operating Temperature	-20...+55°C (Without freeze)
-----------------------	------------------------------

Humidity	15% ... 95%
----------	-------------

Mechanical Protection

IP67


UNASSIGNED

Disegno 2D PDF

1,00E-06

CONNECTIONS


Eletrical diagram



Connector



OTHERS



**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)

**date of
printing**
10/08/2026
04:26:17

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com