



S300-SG-ST2/ST4

951451320

S300-PR-5-G00-EX-SG-ST2

SINGLE BEAM SAFETY SENSORSSAFETY CONTROL UNITS

OVERVIEW

- Installation Flexibility
 - Long distance
 - Low temperature with defogging function
 - 4 safety areas controlled with one unit
 - Double muting
- SENSORS**
- Emitter-receiver photocells with test input
 - Type 2 and Type 4 models
 - Plastic tubular and MAXI formats
 - Up to 50m operating distance
 - Class 1 red laser emission models up to 40
 - Standard M12 connectors
- CONTROL UNITS:**
- Integrated control of 4 single beams and 2 light curtains
 - Simple DIP Swieth configuration
 - Muting functions can be assigned to light curtains or single beams

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0 ... 50 m
Resolution	Single-beam
controlled height	Single-beam

Sensitivity adjustment	n/a
Effective Aperture Angle	$\leq \pm 5^\circ$

Application

Function Principle	Emitter
Control unit to be used	SG-BWS-T4 Series
Description	MAXI Type 2 Safety Photocell Emitter
Optic position	Radial 90°
Functions	Emitter for SG-BWS-T4

Safety parameters

Type	Type 2 safety photocell
PL	n/a

Outputs

Output type	n/a
Switching frequency	
Response time	n/a

Electrical data

Operating Voltage	24 Vdc $\pm 15\%$
No-Load supply current	

Load current	
Output voltage drop	
LED indicators	Green (POWER ON)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	25x85x70
Material	Plastic - PBT / PC
Housing material	PBT Fiber Glass reinforced
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	-25...+70°C
Diameter/Dimension	

Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1 octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	MAXI
Operating Temperature	- 25...+55°C (Without freeze)
Mechanical Protection	IP67

UNASSIGNED

Disegno 2D PDF	n/a
----------------	-----

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
11/08/2026
05:51:21