

S300-SG-ST2/ST4

951451380

S300-PR-5-F00-OC-SG-ST4

SINGLE BEAM SAFETY SENSOR SAFETY CONTROL UNITS



OVERVIEW

- Installation Flexibility
- Long distance
- Low temperature with defogging function
- 4 safety areas controlled with one unit
- Double muting

SENSORS

- Emitter-receiver photocells with test input
- Type 2 and Type 4 models
- Plastic tubular and MAXI formats
- Up to 50m operating distance
- Class 1 red laser emission models up to 40
- Standard M12 connectors

CONTROL UNITS:

- Integrated control of 4 single beams and 2 light curtains
- Simple DIP Switch configuration
- Muting functions can be assigned to light curtains or single beams

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	9 ... 40 m
--------------------------	------------

Resolution	Single-beam
------------	-------------

controlled height	Single-beam
-------------------	-------------

Sensitivity adjustment	Trimmer
Effective Aperture Angle	$\leq \pm 2,5^\circ$

Application

Function Principle	Receiver
Control unit to be used	SG-BWS-T4 Series
Description	MAXI Type 4 Safety Photocell Receiver
Optic position	Radial 90°
Functions	Receiver for SG-BWS-T4

Safety parameters

Type	Type 4 safety photocell
PL	n/a

Outputs

Output type	PNP
Output Function	To be connected to SG-BWS-T4 Safety Control Unit Series
Switching frequency	
Response time	1 ms

Electrical data

Operating Voltage	24 Vdc $\pm 15\%$
-------------------	-------------------

No-Load supply current	
Load current	
Output voltage drop	
LED indicators	Yellow (OUTPUT) - Green (STABILITY)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	n/a
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	25x85x70
Material	Plastic - PBT / PC
Housing material	PBT Fiber Glass reinforced
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	-25...+70°C

Diameter/Dimension	
Vibrations	Width 0.35 mm, frequency 10 ... 55Hz; 20 sweep per axis, 1octave/min (EN 60068-2-6)
Shocks	16 ms (10 G) 1,000 shocks per axis (EN 60068-2-29)

Test/Approvals

Approvals	CE, cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	MAXI
Operating Temperature	- 25...+55°C (Without freeze)
Mechanical Protection	IP67

UNASSIGNED

Disegno 2D PDF	n/a
----------------	-----

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
02/06/2026
19:26:30