

CS&CV Cables

95A252700

CS-A1-03-U-50

THE RIGHT CONNECTION FOR YOUR PHOTOELECTRIC SENSORSFOR INDUSTRIAL ENVIRONMENT 24VDC OR 10-30VDC POWER SUPPLY

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- PVC UL style 2464
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
Sensitivity adjustment	n/a

Application

Description	Straight female
Functions	Cable/connector

Outputs

Output type n/a

Response time n/a

Electrical data

Operating Voltage 10-30 VDC

Emission n/a

Mechanical data

Dimensions	L=50m
Connections	M12 5-poles
Material	PVC UL style 2464

Generical Data

Dimensions L=50m

Datasensing S.r.l.

Strada S.Caterina, 235 41122 Modena (MO) Tel. 059 420411 Fax 059 253973 E-mail info@datasensing.com **date of printing**15/12/2025
02:09:57