

# CS&CV Cables



**95A252840**

**CS-F1-80-B-01**

CASCADE CABLE FOR SG4 EXTENDED

## OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	n/a
controlled height	n/a
Sensitivity adjustment	n/a

### Application

Description	Extension cable
-------------	-----------------

Functions	SG Programmable cascading
Safety parameters	
Type	Safety accessory
Outputs	
Output type	n/a
Response time	n/a
Electrical data	
Operating Voltage	n/a
Emission	n/a
Mechanical data	
Dimensions	L=1m
Connections	n/a
Material	Plastic - PVC
Generical Data	
Dimensions	L=1m

**Datasensing  
S.r.l.**  
Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
10/01/2026  
02:05:21

