



# CS&CV Cables

95A252910

CS-G1-60-B-002

PIGTAIL CABLE FOR SG4-14/30-XXXX-OO-N

## OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	n/a
controlled height	n/a
Sensitivity adjustment	n/a

### Application

Description	Extension cable
-------------	-----------------

Functions	SG adapter to SE pin-out
-----------	--------------------------

#### Safety parameters

Type	Safety accessory
------	------------------

#### Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

#### Electrical data

Operating Voltage	n/a
-------------------	-----

Emission	n/a
----------	-----

#### Mechanical data

Dimensions	L=0.2m
------------	--------

Connections	n/a
-------------	-----

Material	Plastic - PVC
----------	---------------

#### Generical Data

Dimensions	L=0.2m
------------	--------

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
27/04/2026  
05:30:36

