



CS&CV Cables

95ACC1510

CV-A1-26-B-03

THE RIGHT CONNECTION FOR YOUR PHOTOELECTRIC
SENSORS FOR INDUSTRIAL ENVIRONMENT 24VDC OR
10-30VDC POWER SUPPLY

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8, 12 or 17 poles
- Shielded or unshielded models
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
--------------------------	-----

Sensitivity adjustment	n/a
------------------------	-----

Application

Description	Straight female shielded
-------------	--------------------------

Functions	Cable/connector
-----------	-----------------

Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

Electrical data

Operating Voltage	10-30 VDC
-------------------	-----------

Emission	n/a
----------	-----

Mechanical data

Dimensions	L=3m
------------	------

Material	PVC (Black)
----------	-------------

Connections	M12 8-poles
-------------	-------------

Generical Data

Dimensions	L=3m
------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
12/06/2026
04:16:33