



CS&CV Cables

95ASE1230

CS-A1-06-U-05

CONNECTION CABLE 8 POLES WITH M12 AXIAL CONNECTOR

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
controlled height	n/a
Sensitivity adjustment	n/a

Application

Description	Straight female
-------------	-----------------

Functions

Cable/connector

Safety parameters

Type

Safety accessory

Outputs

Output type

n/a

Response time

n/a

Electrical data

Operating Voltage

10-30 VDC

Emission

n/a

Mechanical data

Dimensions

L=5m

Connections

M12 8-poles

Material

PVC UL style 2464

Generical Data

Dimensions

L=5m

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
07/04/2026
07:34:41

