



SG-IP69K

95ASE1340

SG-IP69K-900
IP69K PROTECTION FOR H=900

OVERVIEW

TECHNICAL FEATURES

Detection properties

| | |
|--------------------------|-----|
| Nominal sensing distance | n/a |
|--------------------------|-----|

| | |
|-------------------|-----|
| controlled height | n/a |
|-------------------|-----|

| | |
|------------------------|-----|
| Sensitivity adjustment | n/a |
|------------------------|-----|

Application

| | |
|-------------|-----------------------------|
| Description | Clear tube wash-down design |
|-------------|-----------------------------|

| | |
|-----------|----------------------------|
| Functions | IP69K protection for H=900 |
|-----------|----------------------------|

Safety parameters

| | |
|------|------------------|
| Type | Safety accessory |
|------|------------------|

Outputs

| | |
|---------------|-----|
| Output type | n/a |
| Response time | n/a |

Electrical data

| | |
|-------------------|-----|
| Operating Voltage | n/a |
| Emission | n/a |

Mechanical data

| | |
|-------------|----------------|
| Dimensions | Ø70x1121 |
| Connections | n/a |
| Material | Plastic - PMMA |

Generical Data

| | |
|------------|----------|
| Dimensions | Ø70x1121 |
|------------|----------|

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
22/04/2026
19:06:52