


NX



NX16SR/XCP-A010

Area Sen,h=157mm-10mm pitch,E+R

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,5 ... 2m
--------------------------	------------

Beams space	10mm
-------------	------

controlled height	150mm
-------------------	-------

minimum detectable object	Ø 5mm
---------------------------	-------

Outputs

Output Function	NC
-----------------	----

Switching frequency	130Hz
---------------------	-------

Electrical data

No-Load supply current	150mA (emitter) - 25mA (receiver)
------------------------	-----------------------------------

Load current	100mA
--------------	-------

Leakage current	< 10μA @ 26V
Output voltage drop	≤2V@100mA
Max ripple content	10%
LED indicators	emitter: yellow (poweON and emission active) - receiver: red (signal level) - yellow (output state active)
Emission	Infrared (880nm)
Interference to external light	1000lux (incandescent light) - 1500lux (sunlight)

Mechanical data

Connections	With PCB connectors / Emitter, Conn. 3 MOLEX 22-05-7038 - Positive, Check, Common / Receiver, Conn. 1 MOLEX 22-05-7038 - Positive, Check, Common / Receiver, Conn. 2 MOLEX 22-05-7048 Positive, Check, Output, Common
-------------	---

Generical Data

Dimensions	157x36x18
Mechanical Protection	Not defined

Datasensing
S.r.l.
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of
printing
10/08/2026
06:48:53