



DS1

957701180

DS1-SD-SR-015-JV

AREASCAN™ DETECTION AND MEASUREMENT LIGHT GRIDS WITH ANALOG OUTPUT

OVERVIEW

- 4 mm resolution and 1 ms response time
- 100 to 300 mm controlled height
- Operating distance up to 4 m
- PNP digital and 0-10 V analog outputs
- Adjustment trimmer

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,15..1m
controlled height	150mm
minimum detectable object	7mm
number of rays	24
Sensitivity adjustment	n/a

Application

Function Principle	Emitter- Receiver
Description	Slim profile - Low res. 7 mm
Functions	Light array for detection and measurement

Outputs

Output type	PNP, 0-10 V
Output Function	NO; 0...10V
Response time	1ms

Electrical data

Operating Voltage	20,4...27,6VDC
No-Load supply current	$\leq 200\text{mA}$
Load current	$\leq 100\text{mA}$
Output voltage drop	$\leq 1,5\text{V}$ $I_{\text{load}} = 100\text{mA}$
LED indicators	Yellow (output state) Green (powerON)
Emission	Infrared (880nm)

Mechanical data

Dimensions	22x200x43
Weight	400g
Housing Material	Aluminium
Connections	M12 Plug

Active Head Material	PMMA
----------------------	------

Material	Metal - Aluminium / PMMA
----------	--------------------------

Test/Approvals

Approvals	CE cULus
-----------	----------

Accessories

Supplied Accessories	Fixing brackets
----------------------	-----------------

Generical Data

Dimensions	22x200x43
------------	-----------

Operating Temperature	0°C...+ 50° C
-----------------------	---------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
05/04/2026
17:32:58