



CQ55

CQ55/BP-3E

Cap.35x57x15,PNP-NO+NC,M12
plug,Sch/Nsch-LD
15 X 35 X 55 MM CUBIC CAPACITIVE SENSORS

OVERVIEW

- DC supply voltage
- Adjustable sensitivity
- Flat polycarbonate plastic housing

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	4...25mm
Thermal drift of Sr	< 20%
Repeat Accuracy	5%
Sensitivity adjustment	Yes
Hysteresis	≤ 20%

Outputs

Output type	PNP
-------------	-----

Output Function	NO + NC
Switching frequency	50Hz
Electrical data	
Operating Voltage	10...40Vdc
No-Load supply current	$\leq 10\text{mA}$
Load current	$\leq 200\text{mA}$
Leakage current	$\leq 10\mu\text{A}$
Output voltage drop	2,5Vmax @IL=200mA
Max ripple content	$\leq 10\%$
LED indicators	Yellow LED (object detected)
Time delay before availability	$\leq 100\text{ms}$
Short-circuit protection	Yes, autoreset
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes
Mechanical data	
Dimensions	55x35x15mm
Mounting	Shielded/Unshielded
Housing material	PC

Weight	65g
Connections	M12 plug
Active Head Material	PC
Operating temperature	-25°C...+80°C (without freeze)
Storage temperature	-40°C...+85°C
Diameter/Dimension	55x35x15mm

Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Degree of protection	IP67

Accessories

Supplied Accessories	screw driver
----------------------	--------------

Generical Data

Dimensions	55x35x15mm
Operating Temperature	-25°C...+80°C (without freeze)
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)

**date of
printing**
13/06/2026
11:43:21

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com