



C18FT

C18FT/BP-2EIO

Capacitive sensor M18 DC, Conn., IO-Link, Shield

OVERVIEW

- Sensors for food and beverage applications
- High noise immunity
- IO-Link communication
- ECOLAB certified sensors
- IP69K mechanical protection



ECOLAB® IO-Link



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	8mm
Thermal drift of Sr	< 20%
Repeat Accuracy	5%
Sensitivity adjustment	Yes
Hysteresis	≤ 20%

Outputs

Output type	NPN, PNP, Push-pull, IO-Link
-------------	------------------------------

Output Function	NO+NC/IO-Link
-----------------	---------------

Switching frequency	50Hz
---------------------	------

Electrical data

Operating Voltage	10...40Vdc
-------------------	------------

No-Load supply current	$\leq 20\text{mA}$
------------------------	--------------------

Load current	$\leq 200\text{mA}$
--------------	---------------------

Leakage current	$\leq 100\mu\text{A}$
-----------------	-----------------------

Output voltage drop	$\leq 1.0\text{ VDC @ }200\text{ mA DC}$
---------------------	--

Max ripple content	$\leq 10\%$
--------------------	-------------

LED indicators	Yellow LED (object detected), green LED power supply/stability
----------------	--

Time delay before availability	$\leq 300\text{ms}$
--------------------------------	---------------------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Impulsive Overvoltage Protection	Yes
----------------------------------	-----

Mechanical data

Mounting	Shielded
----------	----------

Housing material	PTFE
------------------	------

Weight	62g
Connections	M12 plug
Active Head Material	PTFE
Tightening torque	≤ 1 Nm
Storage temperature	-40°C...+85°C
Diameter/Dimension	M18

Test/Approvals

Approvals	CE cULus IO-Link ECOLAB
EMC compatibility	EN60947-1; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27

Accessories

Supplied Accessories	screw driver, 2 x M18 nuts
----------------------	----------------------------

Generical Data

Dimensions	M18 / L = 85mm
Operating Temperature	-30°C...+85°C (without freeze)
Mechanical Protection	IP68, IP69K

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

10/08/2026
01:31:24