

Stainless steel

95B061031



IS-05-A3-S1
CABLE/CONNECTOR

OVERVIEW

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,8mm
Operanting distance	0...0,65mm
Standard target	5x5mm FE360
Correction Factor	copper: 0,2...0,5 / aluminium: 0,3...0,5 / brass: 0,4...0,6 / staineis steel: 0,7...0,9
Repeat Accuracy	< 1% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 15%

Application

Description	M5 standard flush mount
-------------	-------------------------

Functions	Proximity
-----------	-----------

Outputs	
Output type	NPN
Output Function	NO
Switching frequency	2kHz
Response time	0,25

Electrical data	
Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	100mA
Output voltage drop	< 1,5V
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data	
Dimensions	Ø5x40

Mounting	Shielded
Material	Stainless steel
Housing material	Stainless steel
Connections	M8 Plug
Active Head Material	POM
Tightening torque	1,5Nm
Diameter/Dimension	M5

Test/Approvals

Approvals	CE
-----------	----

Accessories

Supplied Accessories	2 nuts M5x0.5
----------------------	---------------

Generical Data

Dimensions	Ø5 / L = 40mm
Operating Temperature	-25°C...+70°C
Mechanical Protection	IP69K

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411

date of printing

10/08/2026
04:13:30

Fax 059 253973
E-mail
info@datasensing.com