

AC1



AC6/AP-1A86

Ind.d4,PNP-NO,Cable,Sch-STD

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0,8mm
Operanting distance	0...0,65mm
Standard target	4x4mm FE360
Correction Factor	copper: $0,28 \pm 10\%$ / aluminium: $0,21 \pm 10\%$ / brass: $0,32 \pm 10\%$ / stainless steel: $0,63 \pm 10\%$
Thermal drift of Sr	< 10%
Repeat Accuracy	< 5% (UB 24V Ta=23°C $\pm 5^{\circ}\text{C}$)
Hysteresis	1 ... 20%

Application

Description	Ø4 short case flush mount
Functions	Proximity

Outputs	
Output type	PNP
Output Function	NO
Switching frequency	5kHz

Electrical data	
Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	≤ 100mA
Leakage current	≤ 10μA
Output voltage drop	≤ 1,5V @100mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes
Protection against inductive loads	Yes

Mechanical data	

Mounting	Shielded
Material	AISI303 Stainless Steel
Housing material	AISI303 Stainless Steel
Connections	5m PVC Cable
Active Head Material	PBT
Diameter/Dimension	Ø4

Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27

Generical Data

Dimensions	Ø4 / L = 24,9mm
Operating Temperature	-25°C...+70°C
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
07/08/2026
01:17:18