

Basic



95B061131

IS-08-A1-S2

**NON-CONTACT DETECTION COST EFFECTIVE AND
RELIABLE DETECTION OF ANY METAL PART**

OVERVIEW

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	1,5mm
Operanting distance	0...1,21mm
Standard target	8x8mm FE360
Correction Factor	copper: 0,2...0,5 / aluminium: 0,3...0,5 / brass: 0,4...0,6 / staineless steel: 0,7...0,9
Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 10%

Application

Description	M8 standard flush mount
-------------	-------------------------

Functions	Proximity
Outputs	
Output type	PNP
Output Function	NO
Switching frequency	1kHz
Response time	0,5
Electrical data	
Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	200mA
Output voltage drop	≤ 1,2V @100mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data

Dimensions	Ø8x69
------------	-------

Mounting	Shielded
----------	----------

Material	Nickel-plated brass
----------	---------------------

Housing material	Nickel-plated brass
------------------	---------------------

Connections	M12 Plug
-------------	----------

Active Head Material	LCP
----------------------	-----

Tightening torque	2Nm
-------------------	-----

Diameter/Dimension	M8
--------------------	----

Test/Approvals

Approvals	CE cULus
-----------	----------

Accessories

Supplied Accessories	2 nuts M8x1
----------------------	-------------

Generical Data

Dimensions	Ø8 / L = 69mm
------------	---------------

Operating Temperature	-25°C...+70°C
-----------------------	---------------

Mechanical Protection	IP67
-----------------------	------

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

10/08/2026
03:28:18