# Basic



## 95B063341

### IS-12-G4-03

**NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART**

# OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

# TECHNICAL FEATURES

Detection properties

| | |
|---|---|
| Nominal sensing distance | 4mm |
| Operanting distance | 0…3,24mm |
| Standard target | 12x12mm FE360 |
| Correction Factor | copper: 0,2…0,5 / aluminium: 0,3…0,5 / brass: 0,4…0,6 / stainelss steel: 0,7…0,9 |

| | |
|---|---|
| Repeat Accuracy | < 3% (UB 24V Ta=23°C ±5°C) |
| Hysteresis | < 10% |

Application

| | |
|---|---|
| Description | M12 short case flush mount |
| Functions | Proximity |

Outputs

| | |
|---|---|
| Output type | NPN |
| Output Function | NC |
| Switching frequency | 500Hz |
| Response time | 1 |

Electrical data

| | |
|---|---|
| Operating Voltage | 10...30Vdc |
| No-Load supply current | ≤ 10mA |
| Load current | 200mA |
| Output voltage drop | ≤ 1,2V @100mA |
| Max ripple content | ≤ 10% |
| LED indicators | Yellow LED output state |
| Time delay before availability | ≤ 75ms |
| Short-circuit protection | Yes |

| | |
|---|---|
| Reverse Polarity Protection | Yes |
| Emission | ≥100kHz |
| Protection against inductive loads | Yes |

Mechanical data

| | |
|---|---|
| Dimensions | Ø12x43 |
| Mounting | Shielded |
| Material | Nickel-plated brass |
| Housing material | Nickel-plated brass |
| Connections | 2m PVC Cable |
| Active Head Material | LCP |
| Tightening torque | 6Nm |
| Diameter/Dimension | M12 |

Test/Approvals

| | |
|---|---|
| Approvals | CE cULus ECOLAB DIVERSEY |

Accessories

| | |
|---|---|
| Supplied Accessories | 2 nuts M12x1 |

Generical Data

| | |
|---|---|
| Dimensions | Ø12 / L = 43mm |

| | |
|---|---|
| Operating Temperature | -25°C…+70°C |
| Mechanical Protection | IP67 |

**Datasensing S.r.l.**
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of printing**
03/11/2026
06:34:27