

# Basic



**95B063531**

**IS-18-G1-S2**

**NON-CONTACT DETECTION COST EFFECTIVE AND  
RELIABLE DETECTION OF ANY METAL PART**

## OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversy certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	8mm
Operanting distance	0...6,48mm
Standard target	24x24mm FE360
Correction Factor	copper: 0,2...0,5 / aluminium: 0,3...0,5 / brass: 0,4...0,6 / staineless steel: 0,7...0,9

Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
-----------------	----------------------------

Hysteresis	< 10%
------------	-------

### Application

Description	M18 short case flush mount
-------------	----------------------------

Functions	Proximity
-----------	-----------

### Outputs

Output type	PNP
-------------	-----

Output Function	NO
-----------------	----

Switching frequency	400Hz
---------------------	-------

Response time	1,25
---------------	------

### Electrical data

Operating Voltage	10...30Vdc
-------------------	------------

No-Load supply current	≤ 10mA
------------------------	--------

Load current	200mA
--------------	-------

Output voltage drop	≤ 1,2V @100mA
---------------------	---------------

Max ripple content	≤ 10%
--------------------	-------

LED indicators	Yellow LED output state
----------------	-------------------------

Time delay before availability	≤ 75ms
--------------------------------	--------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	≥100kHz
----------	---------

Protection against inductive loads	Yes
------------------------------------	-----

#### Mechanical data

Dimensions	Ø18x56
------------	--------

Mounting	Shielded
----------	----------

Material	Nickel-plated brass
----------	---------------------

Housing material	Nickel-plated brass
------------------	---------------------

Connections	M12 Plug
-------------	----------

Active Head Material	LCP
----------------------	-----

Tightening torque	20Nm
-------------------	------

Diameter/Dimension	M18
--------------------	-----

#### Test/Approvals

Approvals	CE cULus ECOLAB DIVERSEY
-----------	--------------------------

#### Accessories

Supplied Accessories	2 nuts M18x1
----------------------	--------------

#### Generical Data

Dimensions	Ø18 / L = 56mm
------------	----------------

Operating Temperature

-25°C...+60°C

Mechanical Protection

IP67

**Datasensing  
S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
15/06/2026  
19:49:15