Basic



95B063701

IS-30-G2-03

NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART

OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	15mm
Operanting distance	0…12,1mm
Standard target	45x45mm FE360
Correction Factor	copper: 0,2…0,5 / aluminium: 0,3…0,5 / brass: 0,4…0,6 / stainelss steel: 0,7…0,9

Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 10%

Application

Description	M30 short case flush mount
Functions	Proximity

Outputs

Output type	PNP
Output Function	NC
Switching frequency	200Hz
Response time	2,5

Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	200mA
Output voltage drop	≤ 1,2V @100mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 75ms
Short-circuit protection	Yes

Reverse Polarity Protection	Yes
Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data

Dimensions	Ø30x49
Mounting	Shielded
Material	Nickel-plated brass
Housing material	Nickel-plated brass
Connections	2m PVC Cable
Active Head Material	LCP
Tightening torque	40Nm
Diameter/Dimension	M30

Test/Approvals

Approvals	CE cULus ECOLAB DIVERSEY

Accessories

Supplied Accessories	2 nuts M30x1.5

Generical Data

Dimensions	Ø30 / L = 49mm

Operating Temperature	-25°C…+70°C
Mechanical Protection	IP67

Datasensing S.r.l.
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of printing
04/11/2026
03:45:56