

# Basic



**95B066880**

**IS-08-G2-S1**

**NON-CONTACT DETECTION COST EFFECTIVE AND  
RELIABLE DETECTION OF ANY METAL PART**

## OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversy certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	2mm
Operanting distance	0...1,62mm
Standard target	8x8mm FE360
Correction Factor	copper: 0,2...0,5 / aluminium: 0,3...0,5 / brass: 0,4...0,6 / staineless steel: 0,7...0,9

Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
-----------------	----------------------------

Hysteresis	< 10%
------------	-------

### Application

Description	M8 short case flush mount
-------------	---------------------------

Functions	Proximity
-----------	-----------

### Outputs

Output type	PNP
-------------	-----

Output Function	NC
-----------------	----

Switching frequency	500Hz
---------------------	-------

Response time	1
---------------	---

### Electrical data

Operating Voltage	10...30Vdc
-------------------	------------

No-Load supply current	≤ 10mA
------------------------	--------

Load current	200mA
--------------	-------

Output voltage drop	≤ 1,2V @100mA
---------------------	---------------

Max ripple content	≤ 10%
--------------------	-------

LED indicators	Yellow LED output state
----------------	-------------------------

Time delay before availability	≤ 75ms
--------------------------------	--------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	≥100kHz
----------	---------

Protection against inductive loads	Yes
------------------------------------	-----

#### Mechanical data

Dimensions	Ø8x50
------------	-------

Mounting	Shielded
----------	----------

Material	Nickel-plated brass
----------	---------------------

Housing material	Nickel-plated brass
------------------	---------------------

Connections	M8 Plug
-------------	---------

Active Head Material	LCP
----------------------	-----

Tightening torque	2Nm
-------------------	-----

Diameter/Dimension	M8
--------------------	----

#### Test/Approvals

Approvals	CE cULus
-----------	----------

#### Accessories

Supplied Accessories	2 nuts M8x1
----------------------	-------------

#### Generical Data

Dimensions	Ø8 / L = 50mm
------------	---------------

Operating Temperature

-25°C...+60°C

Mechanical Protection

IP67

**Datasensing  
S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
16/06/2026  
02:37:45