

# Metal Face



**95B063871**

**IS-12-L1-S2**

**NON-CONTACT DETECTION COST EFFECTIVE AND  
RELIABLE DETECTION OF ANY METAL PART**

## OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	4mm
Operanting distance	0...3,24mm
Standard target	12x12mm FE360
Correction Factor	copper: 0,4 / aluminium: 0,45 / brass: 0,5 / staineless steel: 0,85

Repeat Accuracy	< 1% (UB 24V Ta=23°C ±5°C)
-----------------	----------------------------

Hysteresis	< 15%
------------	-------

### Application

Description	M12 metal face no-flush mount
-------------	-------------------------------

Functions	Proximity
-----------	-----------

### Outputs

Output type	PNP
-------------	-----

Output Function	NO
-----------------	----

Switching frequency	1kHz
---------------------	------

Response time	0,5
---------------	-----

### Electrical data

Operating Voltage	10...30Vdc
-------------------	------------

No-Load supply current	≤ 10mA
------------------------	--------

Load current	200mA
--------------	-------

Output voltage drop	≤ 1,5V @100mA
---------------------	---------------

Max ripple content	≤ 10%
--------------------	-------

LED indicators	Yellow LED output state
----------------	-------------------------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	≥100kHz
----------	---------

Protection against inductive loads	Yes
------------------------------------	-----

#### Mechanical data

Dimensions	Ø12x68
------------	--------

Mounting	Unshielded
----------	------------

Material	Stainless steel
----------	-----------------

Housing material	Stainless steel
------------------	-----------------

Connections	M12 Plug
-------------	----------

Active Head Material	Stainless steel AISI303
----------------------	-------------------------

Tightening torque	6Nm
-------------------	-----

Diameter/Dimension	M12
--------------------	-----

#### Test/Approvals

Approvals	CE
-----------	----

#### Accessories

Supplied Accessories	2 nuts M12x1
----------------------	--------------

#### Generical Data

Dimensions	Ø12 / L = 68mm
------------	----------------

Operating Temperature	-25°C...+70°C
-----------------------	---------------

**Datasensing  
S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
15/06/2026  
22:02:10