

NAMUR

95B066780



IS-08-A20-S1

IEP58 PROGRAMMING TOOL

OVERVIEW

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	1mm
Operanting distance	0...0,81mm
Standard target	8x8mm FE360
Correction Factor	copper: 0,2...0,5 / aluminium: 0,3...0,5 / brass: 0,4...0,6 / stainelss steel: 0,7...0,9
Repeat Accuracy	< 3% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 10%

Application

Description	M8 NAMUR flush mount
-------------	----------------------

Functions	Proximity
-----------	-----------

Outputs	
Output type	NAMUR
Output Function	NAMUR
Switching frequency	2kHz
Response time	0,25

Electrical data	
Operating Voltage	7,7...9Vdc
No-Load supply current	< 1mA (target absent)
Load current	< 3mA (target present)
Max ripple content	≤ 10%
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data	
Dimensions	Ø8x48
Mounting	Shielded
Material	Nickel-plated brass

Housing material	Nickel-plated brass
------------------	---------------------

Connections	M8 Plug
-------------	---------

Active Head Material	LCP
----------------------	-----

Tightening torque	2Nm
-------------------	-----

Diameter/Dimension	M8
--------------------	----

Test/Approvals

Approvals	CE cULus
-----------	----------

Accessories

Supplied Accessories	2 nuts M8x1
----------------------	-------------

Generical Data

Dimensions	Ø8 / L = 48mm
------------	---------------

Operating Temperature	-25°C...+60°C
-----------------------	---------------

Mechanical Protection	IP67
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
00:47:16