



AK

AK1/CP-1A8R

Ind.M18,PNP-NC,Cable,Sch-STD

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	5mm
Operanting distance	0...4,05mm
Standard target	18x18mm FE360
Correction Factor	copper: 0,40 / aluminium: 0,48 / brass: 0,50 / stainless steel: 0,86
Thermal drift of Sr	< 10%
Repeat Accuracy	< 5% (UB 24V Ta=23°C ±5°C)
Hysteresis	1 ... 20%

Application

Description	M18 standard flush mount
Functions	Proximity

Outputs

Output type	PNP
Output Function	NC
Switching frequency	600Hz

Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	$\leq 20\text{mA}$
Load current	$\leq 400\text{mA}$
Leakage current	$\leq 10\mu\text{A}$
Output voltage drop	$\leq 1\text{V @}400\text{mA}$
Max ripple content	$\leq 10\%$
LED indicators	Yellow LED output state
Time delay before availability	$\leq 50\text{ms}$
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes
Protection against inductive loads	Yes

Mechanical data

Mounting	Shielded
----------	----------

Material	Nickel-plated brass
Housing material	Nickel-plated brass
Connections	10m PVC Cable
Active Head Material	PBT
Tightening torque	25Nm
Diameter/Dimension	M18

Test/Approvals

Approvals	CE UR
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27

Accessories

Supplied Accessories	2 nuts M18x1
----------------------	--------------

Generical Data

Dimensions	M18 x 1 / L = 50mm
Operating Temperature	-25°C...+70°C
Mechanical Protection	IP67

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

10/08/2026
02:58:02