



AK

AK1/BP-3H4W

Ind.M18,PNP-NO+NC,M12 Plug,Sch-LD

TECHNICAL FEATURES

Detection properties

Nominal sensing distance

8mm

Operanting distance

0...6,48mm

Standard target

24x24mm FE360

Correction Factor

copper: 0,40 / aluminium: 0,45 / brass: 0,50 / stainless steel: 0,75

Thermal drift of Sr

< 10%

Repeat Accuracy

< 5% (UB 24V Ta=23°C ±5°C)

Hysteresis

1 ... 20%

Application

Description

M18 standard flush mount

Functions

Proximity

Outputs

Output type	PNP
Output Function	NO + NC
Switching frequency	300Hz

Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	≤ 20mA
Load current	≤ 400mA
Leakage current	≤ 10μA
Output voltage drop	≤ 1V @400mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes
Protection against inductive loads	Yes

Mechanical data

Mounting	Shielded
----------	----------

Material	AISI303 Stainless Steel
Housing material	AISI303 Stainless Steel
Connections	M12 Plug
Active Head Material	PBT
Tightening torque	25Nm
Diameter/Dimension	M18

Test/Approvals

Approvals	CE UR
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27

Accessories

Supplied Accessories	2 nuts M18x1
----------------------	--------------

Generical Data

Dimensions	M18 x 1 / L = 64mm
Operating Temperature	-25°C...+70°C
Mechanical Protection	IP67

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com