


Square



95B065250

IS-40-W7-S3
NON-CONTACT DETECTION COST EFFECTIVE AND
RELIABLE DETECTION OF ANY METAL PART

OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	15mm
Operanting distance	0...12,1mm
Standard target	45x45mm FE360
Correction Factor	copper: 0,4 / aluminium: 0,45 / brass: 0,5 / staineless steel: 0,85

Repeat Accuracy	< 1% (UB 24V Ta=23°C ±5°C)
-----------------	----------------------------

Hysteresis	< 15%
------------	-------

Application

Description	Large block style no-flush mount
-------------	----------------------------------

Functions	Proximity
-----------	-----------

Outputs

Output type	NPN/PNP
-------------	---------

Output Function	NO
-----------------	----

Switching frequency	25Hz AC / 40Hz DC
---------------------	-------------------

Response time	20
---------------	----

Electrical data

Operating Voltage	20...250Vac/50...60Hz
-------------------	-----------------------

No-Load supply current	≤ 2,5mA
------------------------	---------

Load current	200mA
--------------	-------

Output voltage drop	< 10Vac ; < 8Vdc
---------------------	------------------

Max ripple content	≤ 10%
--------------------	-------

LED indicators	Yellow LED output state
----------------	-------------------------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data

Dimensions	40x41x118
Mounting	Shielded
Material	Plastic - PBT
Housing material	Plastic - PBT
Connections	Terminal block
Active Head Material	PBT
Diameter/Dimension	40x41x118

Test/Approvals

Approvals	CE
-----------	----

Generical Data

Dimensions	40x41x118mm
Operating Temperature	-25°C...+70°C
Mechanical Protection	IP67

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

10/08/2026
00:17:38