
Square



95B065280

IS-40-Y5-S3

NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART

OVERVIEW

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	30mm
Operanting distance	0…24,3mm
Standard target	90x90mm FE360
Correction Factor	copper: 0,4 / aluminium: 0,45 / brass: 0,5 / stainelss steel: 0,85

Repeat Accuracy	< 1% (UB 24V Ta=23°C ±5°C)
Hysteresis	< 15%

Application

Description	Large block style no-flush mount
Functions	Proximity

Outputs

Output type	PNP
Output Function	NO+NC
Switching frequency	100Hz
Response time	5

Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	200mA
Output voltage drop	≤ 1,5V @100mA
Max ripple content	≤ 10%
LED indicators	Yellow LED output state
Short-circuit protection	Yes
Reverse Polarity Protection	Yes

Emission	≥100kHz
Protection against inductive loads	Yes

Mechanical data

Dimensions	40x41x118
Mounting	Unshielded
Material	Plastic - PBT
Housing material	Plastic - PBT
Connections	Terminal block
Active Head Material	PBT
Diameter/Dimension	40x41x118

Test/Approvals

Approvals	CE

Generical Data

Dimensions	40x41x118mm
Operating Temperature	-25°C…+70°C
Mechanical Protection	IP67

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

01/11/2026
22:09:59