



**P2x**

**937710006**

**P20C 000-000 CM**  
**PUSHING POWER TO THE EDGE**

## OVERVIEW

- qHD (960 x 540) and 2MP (1920 x 1080) resolution imager options both available in monochrome and color
- Field interchangeable lenses, illuminators and filters
- Two embedded illuminator sizes: 14-LED compact and 36-LED high power both integrating TIR lenses to deliver maximum brightness onto the field of view available in 3 different colors (white, blue and red)
- Lens options: Micro-video (6, 8, 12.5 and 17.5mm) or C-Mount
- Innovative 360° software configurable visual feedback
- Top industrial grade: -10 to 50 °C / 14 to 122 °F operating temperature, IP65/67 rating
- Powered by IMPACT software suite with 100+ inspection tools
- Add-on licenses to run even the most advanced Datalogic algorithms



## TECHNICAL FEATURES

Application

Description

Smart camera unit

Electrical data

Led

Power, Busy/Trigger, Out 1; Out 2; Out 3; Online

Mechanical data

Material	Aluminum (housing) and plastic (front head)
Lens mount	C-Mount

### Test/Approvals

Shocks and vibrations	EN 60068-2-6 (14mm@2 to 10Hz; 1.5mm@13 to 55 Hz; 2g @70 to 500Hz; 2h on each axis), EN 60068-2-29 (30g; 6ms; 5000 shocks on each axis), EN 60068-2-27 (30g; 11ms; 3 shocks on each axis)
-----------------------	--

### Generical Data

System Memory	380 MB
Storage	1 GB
Network Interface	1000 Mbit/s Ethernet
Serial Communications	1x RS-232 serial port
Comm Connectivity	Supports EtherNet/IP, Profinet, Modbus TCP
I/O	2 IN / 3 OUT
Power Requirements	24 ± 10% VDC
Dimensions	14 LEDs illuminator: 109 x 54 x 56 mm (4.3 x 2.1 x 2.2in.) 36 LEDs illuminator: 116 x 126 x 70 mm (4.6 x 4.9 x 2.8in.)
Operating Temperature	-10 ... 50°C
Humidity	90% non condensing
Mechanical Protection	IP65/67
Certifications (Safety Compliance)	CE, CSA
Resolution	960x540

Imager	1/2.8" CMOS - Color
Shutter	Global
Frame rate (FPS)	60
Pixel size	5.6 $\mu\text{m}$
C-Mount	Yes

#### Optical Data

Mono/Color	Color
------------	-------

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
13/06/2026  
04:05:17