

# Smart cameras accessories



**93A050140**

**CAB-ETH-X-M10 M12-IP67 GETH-X CAB  
10M**

**PUSHING POWER TO THE EDGE**

## OVERVIEW

- qHD (960 x 540) and 2MP (1920 x 1080) resolution imager options both available in monochrome and color
- Field interchangeable lenses, illuminators and filters
- Two embedded illuminator sizes: 14-LED compact and 36-LED high power both integrating TIR lenses to deliver maximum brightness onto the field of view available in 3 different colors (white, blue and red)
- Lens options: Micro-video (6, 8, 12.5 and 17.5mm) or C-Mount
- Innovative 360° software configurable visual feedback
- Top industrial grade: -10 to 50 °C / 14 to 122 °F operating temperature, IP65/67 rating
- Powered by IMPACT software suite with 100+ inspection tools
- Add-on licenses to run even the most advanced Datalogic algorithms

## TECHNICAL FEATURES

Application

Description

Connecting cable

Mechanical data

Fibre length (m)

10m

**Datasensing  
S.r.l.**

**date of  
printing**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

13/06/2026  
04:25:59