



MS-MP

MSP/00-0A

Photo.M18,NPN/PNP-NO/NC,Cable,Reflex
M18 DECOUT® DC OUTPUT

OVERVIEW

- Wide range of models: diffuse, retro-reflective, polarized, through-beam detection and background suppression
- Through-beam models with high sensing range
- Retro-reflective models with red visible polarized light
- Models with right angle optic (MP)
- Background suppression models with fixed distance
- Check function available for all through-beam models
- Complete protection against electrical damage



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	3,5m
Thermal drift of Sr	$\leq 10\%$ Sr
Repeat Accuracy	5%
Sensitivity adjustment	No

Application

Function Principle

Polarized

Notes

On RL110 reflector

Optic position

Axial

Outputs

Output type

Decout NPN/PNP Selectable NO/NC Selectable

Output Function

NO/NC Selectable

Switching frequency

80Hz

Response time

6,25ms

Electrical data

Operating Voltage

10...30VDC

No-Load supply current

$\leq 30\text{mA}$

Load current

$\leq 100\text{mA}$

Leakage current

$\leq 10\mu\text{A}$

Output voltage drop

$\leq 1,2\text{V}@I_{\text{load}}=100\text{mA}$

Max ripple content

$\leq 10\%$

LED indicators

Red (status output)

Time delay before availability

$\leq 200\text{ms}$

Short-circuit protection

Short circuit (autoreset), Overvoltage

Emission	LED Red (660nm)
Interference to external light	3000lux (incandescent lamp), 10000lux (sunlight)
Impulsive Overvoltage Protection	Impulsive Overvoltage Protection

Mechanical data

Dimensions	M18 x 1 /L =78,9mm
Housing material	PBT / PC cable exit
Weight	70g
Connections	2m PVC cable
Active Head Material	PMMA
Tightening torque	1Nm
Operating temperature	25°C..+ 70° C (Without freeze)
Diameter/Dimension	M18

Test/Approvals

Approvals	CE cURus
EMC compatibility	EN 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27
Degree of protection	IP67

Accessories

||
||
||

Supplied Accessories

nuts M18 x 1

Generical Data

Dimensions

M18 x 1 / L =78,9mm

Operating Temperature



- 25°C...+ 70°C (Without freeze)




Mechanical Protection

IP67

CONNECTIONS


Eletrical diagram






OTHERS

Dimensions



Response curves



**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail

**date of
printing**

10/08/2026
06:27:49

info@datasensing.com