

# S15

952301101

S15-PA-2-G00-XG

PLASTIC AND STAINLESS STEEL TUBULAR M18  
PHOTOELECTRIC SENSORS EVERY ENVIRONMENT



## OVERVIEW

- Short case models for cost and space savings
- Plastic and stainless steel case with IP69K protection
- All optic functions at optimal operating distances
- Models with fixed settings or adjustment trimmer
- Cable, M12 connector and pig-tail models

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	20m
--------------------------	-----

Sensitivity adjustment	n/a
------------------------	-----

### Application

Function Principle	Through beam emitter
--------------------	----------------------

Description	Tubular M18 - axial optic
-------------	---------------------------

Functions	Through beam emitter
-----------	----------------------

## Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

## Electrical data

Operating Voltage	12...30VDC
-------------------	------------

No-Load supply current	$\leq 25\text{mA}$
------------------------	--------------------

Output voltage drop	$\leq 2\text{V}@I_{\text{load}}=100\text{mA}$
---------------------	---

LED indicators	Green (PowerON)
----------------	-----------------

Short-circuit protection	YES
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	LED Infrared
----------	--------------

Interference to external light	according to EN 60947-5-2 : 2020
--------------------------------	----------------------------------

Impulsive Overvoltage Protection	Yes
----------------------------------	-----

Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
-----------------------	---

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

## Mechanical data

Dimensions	Ø18x45
------------	--------

Housing Material	Plastic - PBT / PMMA
------------------	----------------------

Connections	2m cable
-------------	----------

Active Head Material	PMMA
----------------------	------

Storage temperature	- 25°C...+70°C
---------------------	----------------

Material	
----------	--

Diameter/Dimension	M18
--------------------	-----

#### Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

#### Accessories

Supplied Accessories	nuts M18 x 1
----------------------	--------------

#### Generical Data

Dimensions	M18 x 1 /L=45
------------	---------------

Operating Temperature	- 25°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP67
-----------------------	------

### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
01/07/2025  
09:27:50