

P3x



937710034

Smart Camera, P30, Monochrome, 960x540,
120 FPS, 1/2.8" CMOS, Micro Video Lens

OVERVIEW

- qHD (960 x 540) , 2MP (1920 x 1080) and 5MP (2560x1920) resolution imager options both available in monochrome and color
- Field interchangeable lenses, illuminators and filters
- Two embedded illuminator sizes: 14-LED compact and 36-LED high power both integrating TIR lenses to deliver maximum brightness onto the field of view available in 3 different colors (white, blue and red)
- Lens options: Micro-video (6, 8, 12.5 and 17.5mm) or C-Mount
- Innovative 360° software configurable visual feedback
- Top industrial grade: -10 to 50 °C / 14 to 122 °F operating temperature, IP65/67 rating
- Powered by IMPACT software suite with 100+ inspection tools
- Add-on licenses to run even the most advanced Datalogic algorithms

TECHNICAL FEATURES

Application

Description

Smart camera unit

Electrical data

Led

Power, Busy/Trigger, Out 1; Out 2; Out 3; Online

Mechanical data

Material

Aluminum (housing) and plastic (front head)

Lens mount	Micro Video Lenses
------------	--------------------

Test/Approvals

Shocks and vibrations	EN 60068-2-6 (14mm@2 to 10Hz;1.5mm@13 to 55 Hz; 2g @70 to 500Hz; 2h on each axis), EN 60068-2-29 (30g; 6ms; 5000 shocks on each axis), EN 60068-2-27 (30g; 11ms; 3 shocks on each axis)
-----------------------	---

Generical Data

System Memory	380 MB
---------------	--------

Storage	1 GB
---------	------

Network Interface	1000 Mbit/s Ethernet
-------------------	----------------------

Serial Communications	1x RS-232 serial port
-----------------------	-----------------------

Comm Connectivity	Supports EtherNet/IP, Profinet, Modbus TCP
-------------------	--

I/O	2 IN / 3 OUT
-----	--------------

Power Requirements	24 ± 10% VDC
--------------------	--------------

Dimensions	14 LEDs illuminator: 109 x 54 x 56 mm (4.3 x 2.1 x 2.2in.) 36 LEDs illuminator: 116 x 126 x 70 mm (4.6 x 4.9 x 2.8in.)
------------	--

Operating Temperature	-10 ... 50°C
-----------------------	--------------

Humidity	90% non condensing
----------	--------------------

Mechanical Protection	IP65/67
-----------------------	---------

Certifications (Safety Compliance)	CE, CSA
------------------------------------	---------

Resolution	960x540
------------	---------

Imager	1/2.8" CMOS - Mono
Shutter	Global
Frame rate (FPS)	120
Pixel size	5.6 μm

Optical Data

Mono/Color	Monochrome
------------	------------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
04/04/2026
17:05:43