

SL5

952501030

SL5-5-G-82

SINGLE BEAM SAFETY SENSORS SAFETY CONTROL UNITS



OVERVIEW

Installation Flexibility Long distance Low temperature with defogging function 4 safety areas controlled with one unit Double muting SENSORS:

- Emitter-receiver photocells with test input
- Type 2 and Type 4 models
- Plastic tubular and MAXI formats
- Up to 50m operating distance
- Class 1 red laser emission models up to 40
- Standard M12 connectors

CONTROL UNITS:

- Integrated control of 4 single beams and 2 light curtains
- Simple DIP Switch configuration
- Muting functions can be assigned to light curtains or single beams

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	60m
--------------------------	-----

Sensitivity adjustment	n/a
------------------------	-----

Application

Function Principle	Through beam emitter
--------------------	----------------------

Description	Tubular M18 - axial optic
Functions	Through beam emitter

Outputs

Output type	n/a
Response time	0,33

Electrical data

Operating Voltage	10...30VDC
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LASER Red (650nm) class1
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	Ø18x66
Material	
Housing material	Plastic ABS / PMMA

Connections	M12 plug
Active Head Material	PMMA
Diameter/Dimension	M18

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	M18 x 1/L=66mm
Operating Temperature	- 10°C...+ 55°C
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
20/06/2026
04:14:52