

S5N

G5000001



MEK-PROOF

**EXTENDED RANGE OF STANDARD "ONE FOR ALL"
PHOTOELECTRIC TUBULAR M18 SENSORS**

OVERVIEW

TECHNICAL FEATURES

Detection properties

Nominal sensing distance

Sensitivity adjustment

n/a

Application

Function Principle

Diffuse reflection (medium distance, $\leq 600\text{mm}$)

Description

M18 optic head cap

Functions

S5N-M Methyl-Ethil-Keton protection

Outputs

Output type

n/a

Response time	n/a
---------------	-----

Electrical data

Operating Voltage	n/a
-------------------	-----

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	n/a
----------	-----

Mechanical data

Dimensions	Ø22x13
------------	--------

Housing Material	Metal / Glass
------------------	---------------

Connections	n/a
-------------	-----

Material	
----------	--

Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

Generical Data

Dimensions	Ø22x13
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)

**date of
printing**
22/04/2026
04:05:48

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com