

Image:

MV-MQ

MVR/A0-0C

Photo.M18,AC-NO,Cable 90°,Receiver

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	16m
Thermal drift of Sr	≤10%Sr
Repeat Accuracy	5%
Sensitivity adjustment	No

Application

Function Principle	Receiver
Emitter/Receiver	Receiver
Optic position	Axial

Outputs

Output type	TRIAC NO
Output Function	NO
Switching frequency	25Hz

Response time	20ms
---------------	------

Electrical data

Operating Voltage	20...253VAC/50-60Hz
No-Load supply current	≤ 30mARMS
Load current	5...300mARMS
Leakage current	6A
Output voltage drop	≤3V@Iload=300mARMS
Max ripple content	≤10%
LED indicators	Red (status output)
Time delay before availability	≤200ms
Interference to external light	3.000lux (incandescent lamp), 10.000lux (sunlight)

Mechanical data

Housing material	PBT / PC cable exit 90°
Connections	2m PVC cable 90°
Active Head Material	PMMA
Tightening torque	1Nm
Diameter/Dimension	M18

Test/Approvals

--

Approvals

CE cURus

EMC compatibility

EN 60947-5-2

Shocks and vibrations

Vibration IEC 60068-2-6 / Shock IEC 60068-2-27

Accessories

Supplied Accessories

Nuts M18 x 1

Generical Data

Dimensions

M18x1/L=78,6mm

Operating Temperature

- 25°C...+ 70°C (Without freeze)

Mechanical Protection

IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
11/08/2026
02:00:51