



FL

FLIE/00-0C

Photo,8m,Cable 90°,Emitter

**“T-STYLE” HOUSING PHOTOELECTRIC SENSORS WITH
M18 OPTICAL HEAD FOR CAR WASHES**

OVERVIEW



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	8m
--------------------------	----

Sensitivity adjustment	No
------------------------	----

Application

Function Principle	Emitter
--------------------	---------

Notes	(3m for car washes)
-------	---------------------

Emitter/Receiver	Emitter
------------------	---------

Outputs

Output type	
-------------	--

Electrical data	
Operating Voltage	19,2 ... 28,8VDC
LED indicators	Green (RUN)
Time delay before availability	≤200ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	LED Infrared (850nm)
Impulsive Overvoltage Protection	Yes


Mechanical data	
Housing material	PBT + PC
Weight	570 g la coppia
Connections	5m PVC cable
Active Head Material	PC
Tightening torque	1Nm
Operating temperature	-20..60°C (without freeze)
Storage temperature	-30..90°C (without freeze)

Test/Approvals	
Approvals	CE

EMC compatibility	EN 60947-5-2
Degree of protection	IP67 (front-head IP69K)
Generical Data	
Operating Temperature	- 20°C...+ 70°C (Without freeze)
Mechanical Protection	IP67 (front-head IP69K)


CONNECTIONS

Eletrical diagram




OTHERS

Dimensions



Response curves



Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
00:29:53